



FEEL THE PERENNIAL

# GLORY



QUALITY WHAT YOU DESIERS



# TEAK

## **TECHNICAL DETAILS CO EXTRUSION**

LENGTH: 2900mm

WIDTH: 146mm

HIGHT: 22mm



# DEW

## **TECHNICAL DETAILS CO EXTRUSION**

LENGTH: 2900mm

WIDTH: 146mm

HIGHT: 22mm



# WALLNUT

## **TECHNICAL DETAILS CO EXTRUSION**

LENGTH: 2900mm

WIDTH: 146mm

HIGHT: 22mm



# IPE

## **TECHNICAL DETAILS CO EXTRUSION**

LENGTH: 2900mm

WIDTH: 146mm

HIGHT: 22mm



## INSTALLATION

### DECKING INSTALLATION ACCESSORIES



95106.C/R	95105.C/R	95108.C/R	95107.C/R	91203.A30
width 71mm thickness 11mm	width 140mm thickness 10mm	width 140mm thickness 22mm	width 60mm width 60mm	width 50mm thickness 30mm

### INSTALLATION GUIDE



91209.C/R		
width	60mm	-
thickness	52mm	-



The design team of Lvsenwood has designed a variety of solutions on the basis of the original installation, including integrated joist system, integrated stepping system, traceless of screw solution, etc. These innovative solutions have applied for a number of national patents for appearance and utility models. The unique solution of Lvsenwood greatly reduces the sawing and other links in the installation process, making the floor paving effect more uniform and perfect.

### TRACELESS OF SCREWS SYSTEM



With our latest screw drilling design, people can hardly see the difference between it and the decking surface itself. We put one plastic cap similar to decking color covering the screw head.

Decking accessories			
			
91205.0	91204.0	91203.0	91210.0
Plastic decking clip	Stainless steel decking clip	Stainless steel starter clip	Stainless steel mounting clip



## DECKING INSTALLATION GUIDE



### Technical Details:

#### Co Extrusion

**Material** → Wood Plastic Composite

**Surface** → 1 Side: Co-Extrusion

2 Side: Wire-Brushed

#### Decking

**Material** → Wood Plastic Composite

**Surface** → 1 Side: Wood Grain (3D Embossed with wire-Brushed)

2 Side: Groove



Scratching Resistant



Cigarette Burn Resistant



Easy Cleaning



Domestic Chemicals Resistant



Stain Resistant



Friendly to Allergic



Soft Rolls Advisable



Bacteriostatic Property



**EXTERIOR SURFACE THAT PROVIDES COMPLETE & ABSOLUTE PROTECTION FROM ALL TYPE OF WEATHER**